

Since  
**1977**  
Design, Development, Manufacturing

**HBL**  
www.hbl.in

# GEN ON



**Sealed Maintenance Free Pure Lead Tin Battery**

Genon batteries are made with state of the art "Pure Lead Tin Thin Plate" technology to deliver high cranking currents. This ensures a reliable start of the genset in any environmental condition.

Genon is a Sealed Maintenance Free battery, delivered in factory charged and ready to use condition.

## FEATURES

- ❑ High Cranking Current : Smaller battery for the same job
- ❑ Low Self Discharge : Assured start even after idle condition for long duration
- ❑ Maintenance Free : No water top-up and specific gravity checks
- ❑ Terminals with copper alloy : High electrical conductivity  
No corrosion, No wear and tear

## BATTERY MODELS & SELECTION CHART

MODEL	No. of 12V Batteries *	GENSET RATING (KVA)	Battery Dimensions (L X W X H in mm)	Weight (Kg)	CCA as per SAE (Amps)	Conventional Equivalent
GN 32-12	1	7.5, 10	165 x 145 x 210	12.5	420	12V 60Ah
GN 65-12	1	15 to 140	330 x 168 x 200	23.5	650	12V 88 to 150Ah
GN 65-12	2	160 to 380	330 x 168 x 200	23.5	650	12V 120 to 150Ah
GN 100-12	2	500 to 625	410 x 176 x 240	35	1100	12V 180 to 200Ah
GN 160-12	2	750 to 1500	525 x 225 x 240	58	1600	2 x 12V 180 to 200Ah

\* No of batteries depends on starter motor rating / voltage.

Genon batteries complies to international standard IEC 60095-1:2006.

Note: Alternator output voltage must be in between 13.8 to 14.2V for a 12V rating and 27.6 to 28.4V for a 24V rating to prevent damage to battery

# HBL

**HBL Power Systems Limited**  
# 8-2-601, Road No.10, Banjara Hills,  
Hyderabad - 500034, TS, INDIA ,  
E-mail : [contact@hbl.in](mailto:contact@hbl.in),  
website : [www.hbl.in](http://www.hbl.in)

**Dealer details:**

HBL/Genon Export/11.08.16

**For Service : Customer Assistance Number 1 800 425 2939 ( Toll Free )**